

NXT[™] Proximity Credentials

DATA SHEET

For Use With NXT Series Proximity Readers



NXT-C Standard Light Proximity Card

- Wallet friendly thinner than other comparable proximity cards
- Extremely durable
- Industry standard formats
- Unique, non-duplicated
 ID codes
- Lifetime Warranty
- 128 bit Encryption



NXT-I Multi Technology Card ISO Thin, just 0.031"

- (0.8 mm) • Designed for photo
- ID printing
- Can also print Bar Codes
- Unique, non-duplicated
- 128 bit Encryption



NXT-K Proximity Key Ring Tag

- Smallest Proximity Key Ring Tag Available
 Robust and Durable
- Robust and Durable
 Washing Machine Tough
 Unique, non-duplicated
- Onique, non-duplicate
 ID codes
 Lifetime Warranty
- 128 bit Encryption
- 128 bit Encryption



NXT-AP Adhesive Proximity Patch

- Turns virtually anything into a prox credential
- Extremely strong adhesive-Thin patch will not fall off
- Unique, non-duplicated ID codes
- Lifetime Warranty
- 128 bit Encryption

Keri's **NXT-C Standard Light Proximity Card** provides maximum read range performance in a package considerably thinner than other "clamshell" proximity cards. It can be easily carried in a wallet or purse or worn on the clothing with a clip or necklace. These cards are extremely durable and convenient. The are manufactured with a vertical hanging slot punch, and they come with a lifetime warranty.

Keri's **NXT-I Multi Technology Card** allows the user to combine several identification technologies in a single credit card thin credential. The most popular feature of Multi Technology Cards is that they can accept a direct print video image - typically a photograph, bar code, or other user graphic - from most industry dye sublimation printers, to create a custom access credential.

Keri's **NXT-K Proximity Key Ring Tag** provides user convenience in a small, ergonomic, and extremely durable package. The tag is equipped with a brass eyelet for attachment to a key ring that ensures the neck of the tag will not break during the life of the system. Key tags are especially convenient for building entrances where the user still has their car keys in hand. If the system has many interior doors that are secured with a Keri access control system, users often attach the tag to a necklace for easy carrying, especially if the clothing does not have pockets.

Keri's **NXT-AP Adhesive Proximity Patch** offers all the flexibility of other Keri proximity credentials, but in a form factor that allows it to be attached to virtually anything. As with any Keri proximity device, it will read through most non metallic surfaces. Attach it to a wallet or cell phone to create a personalized proximity credential, or use it with an existing photo ID card to create new security credentials without incurring the expense of rebadging. You can also place it on high value inventory items to uniquely identify these items to your security system.

All four Keri Proximity Credentials can be used interchangeably on the same system without worry about ID code duplication or format matching. Also, for security purposes, all NXT credentials use 128 bit encryption between card and reader.



www.kerisys.com

302 Enzo Drive • San Jose, California 95138 • email: sales@kerisys.com Phone: 408-435-8400 • Toll Free: 800-260-5265 • Fax: 408-577-1792

NXT[™] Proximity Credentials

DATA SHEET - Page 2 of 2



Specifications:

Read Range:*

NXT-1R up to 4 inches (10 cm) NXT-3R up to 5 inches (12.5 cm) NXT-5R up to 6 inches (15 cm)

Size:

3.38" H x 2.14" W x 0.059" T Approx. (86 x 54 x 1.5 mm)

Weight:

0.31 oz (8.8 g)

Material: ABS

Temperature / Humidity:

-40° F to 158° F (-40° C to 70° C) 0 - 100% Non Condensing

Color: Off White

Warranty:

The Standard Light Proximity Card comes with a limited lifetime warranty against defects in materials and workmanship.



Specifications:

Read Range:* NXT-1R up to 4 inches (10 cm) NXT-3R up to 5 inches (12.5 cm) NXT-5R up to 6 inches (15 cm)

Size:

3.38" H x 2.14" W x 0.031" T Approx. (86 x 54 x 0.08 mm)

Weight: 0.19 oz (5.5 g)

Material: PVC with a printable gloss surface

Temperature / Humidity:

-40° F to 158° F (-40° C to 70° C) 0 - 100% Non Condensing

Color: Off White

Warranty:

The Standard Light Proximity Card comes with a limited 1 year warranty against defects in materials and workmanship.

NXT-K



Specifications:

Read Range:*

NXT-1Rup to 2 inches (5 cm)NXT-3Rup to 3 inches (7.5 cm)NXT-5Rup to 4 inches (10 cm)

Size:

1.51" H x 1.14" W x 0.115"T Approx. (38 x 29 x 5 mm)

Weight: 0.16 oz (4.5 g)

Material: ABS, brass eyelet

Temperature / Humidity: -40° F to 158° F (-40° C to 70° C) 0 - 100% Non Condensing

0 - 100% Non Condensing

Color: Gray

Warranty:

The Key Ring Tag comes with a limited lifetime warranty against defects in materials and workmanship.

ORDERING INFORMATION:

NXT-AP



Specifications:

Read Range:*

NXT-1Rup to 2 inches (5 cm)NXT-3Rup to 3 inches (7.5 cm)NXT-5Rup to 4 inches (10 cm)

Size:

D = 0.980, T = 0.065 inches Approx. 24.89 x 1.65 mm

Weight: 0.03 oz(0.85 g)

Material: Polycarbonate

Frequency: 125 KHz excitation / 62.5 KHz return

Temperature: -35° C to +50° C

Humidity: 0-100% non-condensing

Color: Gray

Warranty:

The Patch comes with a limited lifetime warranty against defects in materials and workmanship.

Specifications subject to change without notice. Trademarks are the property of their respective owners.

* Read Range is stated in a clean RF and electrical environment with card presented parallel to reader surface.

Model Number NXT-C NXT-I NXT-K

NXT-AP

Description

Clamshell Proximity Card ISO Proximity Card Proximity Key Tag Adhesive Proximity Patch



Presented By:

www.kerisys.com